

Air Compressor Oil

PRODUCT DESCRIPTION:

Air Compressor Oils (ammonia only) are highly refined naphthenic mineral oils designed primarily for the lubrication of compressors in industrial refrigeration systems using ammonia as the refrigerant. They are not recommended for use with halocarbon type refrigerants such as Freon. They are also recommended for certain non-compressor applications such as bearings, gears and low-pressure hydraulic systems operating in low temperature conditions.

Typical Properties

Royal Air Compressor Oils			
Product Number	228	229	Test Method
ISO Grade	68	100	
Viscosity@100°C cSt	6.9	9.0	ASTM D445
Viscosity@40°C cSt	68	104	ASTM D445
Viscosity@100°F SUS	361	556	ASTM D445
Viscosity@220°F SUS	50	57	ASTM D445
Flash Point °F	350	365	ASTM D92
Pour Point °F	-22	-4	ASTM D97
Viscosity Index (VI)	30	35	ASTM D2270
API	30.9	29.6	

Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Health and Safety:

When used for its intended application, this product is not expected to have any adverse health implications. For complete information on safe handling, as well as physical and chemical characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website, www.royalmfg.com, or call 918-584-2671. Do not use this product for purposes other than its intended use. Please be responsible to the environment when disposing of used product.

Packaging options:

