



Power Tech Tractor Hydraulic Fluid

Authenticated Tractor Fluid Dual Range Case & I-H MS

Dual Range for Case & I-H MS 1207-1209-1210-1230 is a superior multi-purpose tractor hydraulic fluid recommended for Case & I-H tractors with combined transmission, differential, wet brakes, hydraulic and hydrostatic systems. This product is a special blend of selected high quality paraffinic base oil, high performance additives and a shear stable viscosity index improver. This fluid is designed to prevent wear in the heavily loaded transmission and differential gear assembly. It also provides the high viscosity performance required by today's tractors to handle demanding field conditions. This product meets Case and I-H specifications: MS-1209/Hy-Tran Ultra, MS-1207/Hy-Tran Plus, MS-1210/TCH, MS 1204/TFD Fluid, MS 1205/TFD-II Fluid, MS-1206/PTF Fluid, Case MAT3509 MS-1230, JIC 145, Hy-Tran.

Typical Properties

Dual Range for Case & I-H MS

Product Number	255E	Test Method
API	30.48	-
Flash Point@°C	204	ASTM D92
Pour Point@°C	-48	ASTM D97
Color	<3.0	ASTM D1500
Viscosity@40°C, cSt	59	ASTM D445
Viscosity@100°C, cSt	9.35	ASTM D445
Viscosity Index (VI)	141	ASTM D2270

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice.




1 Gal Jugs



5 Gal Pails



55 Gal. Drums



275/330 Gal Drums



>2000 Gal Bulk

Health and Safety:

This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website.

www.royalmfg.com or call (918)-584-2671.

