



Product Data Sheet



Powertech Type C-2/C-3

Torque Fluid

PRODUCT DESCRIPTION:

Powertech Type C-2/C-3 Torque Fluid is a torque fluid designed specifically for transmissions and torque converters that require an Allison C-3 fluid, including Allison CL(B) T-700 transmissions used in heavy duty trucks, buses and earth moving equipment.

Typical Properties

Powertech Type C-2/C-3 Torque Fluid		
Product Number	209	Test Method
API Gravity	29.5	-
Lbs/Gal		-
Flash Point °C	420	ASTM D92
Pour Point °C	-22	ASTM D97
Color, ASTM	2.0	ASTM D1500
Viscosity@100°F SUS	220	
Viscosity@210°F SUS	48	
Viscosity@100°C, cSt	6.4	ASTM 7042
Viscosity@40°C, cSt	42.7	ASTM D445
Viscosity Index (VI)	98	ASTM D2270

Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Health and Safety:

When used for its intended application, this product is not expected to have any adverse health implications. For complete information on safe handling, as well as physical and chemical characteristics please refer to the Safety Data Sheet (MSDS) found on our website, www.royalmfg.com, or call 918-584-2671. Do not use this product for purposes other than its intended use. Please be responsible to the environment when disposing of used product.

