



707 Moly Gear Lube GL-5

High Performance Gear Lubricant

707 Moly Gear Lube GL-5 has the amazing ability to not only lubricate with a higher margin of protection - rear axles, manual transmissions, bearings and gears but the product can increase fuel economy as well.

707 Moly Gear Lube GL-5 has a wide working temperature range which permits the product to be used throughout the year. This product is complete with extreme pressure capabilities for heavily loaded gears along with excellent oxidation stability for high temperature operation. Inhibitors provide excellent moisture corrosion protection. This product meets MIL-L-2105C, a standard most often required by heavy duty equipment manufacturers.

707 Moly Gear Lube GL-5 is an outstanding product that can be used as a basic gear lubricant for both differentials and manual transmission. It provides high performance protection while reducing the need for separate products and chances of misapplication.

Product Features:

- Used for both differentials and manual transmissions

Customer Benefits:

- Meets MIL-L-2105C
- Cost effective

Applications:

- For use in rear axles, manual transmissions, bearings and gears





Typical Properties


707 Moly Gear Lube GL-5 85W140

Product Number	275	Test Method
API	25.98	-
Specific Gravity	0.8985	ASTM 4052
Lbs./Gal	7.483	-
Density	0.8980	-
Flash Point °C	279	ASTM D97
Pour Point °C	-30	ASTM D97
Color	<3.0	ASTM D1500
Viscosity@ 100°C, cSt	27.52	ASTM 7042
Viscosity@ 40°C, cSt	364.2	ASTM D445
Viscosity Index (VI)	102	ASTM D2270

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice.

Health and Safety: This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Safety Data Sheet (SDS) found on our website. www.royalmfg.com or call (918)-584-2671.

Packaging options:



55 Gal. Drums



275/330 Gal. Totes



>2,000 Gal. Bulk

