



# Product Data Sheet



## ROYAL CHAIN BAR OIL

### PRODUCT DESCRIPTION:

**Chain and Guide Bar Oil** is an all-season multi-viscosity lubricant made especially for use in chain saws. It contains special tackiness additives to cling to the bar and chain and resist “sling-off”. It also contains an anti-wear additive and a potent anti-rust additive to prevent corrosion. This all season oil is recommended for use in all brands of chain saws, including Homelite, Poulan, John Deere, Stihl, McCullough, Husqvarna, Remington, Disston and others.

### KEY FEATURES:

- Tackiness additives
- Multi season

### CUSTOMER BENEFITS:

- Anti-rust additive to prevent corrosion

APPLICATIONS: Chain saws

### PACKAGING:

Totes and Drums





## Typical Properties

### Royal Chain and Guide Bar Oil

Product Number	645	Test Method
API	32.22	-
Specific Gravity	0.86429	ASTM 4052
Lbs./Gal	7.198	-
Density	0.8638	-
Flash Point °C	214	ASTM D92
Pour Point °C	-18	ASTM D97
Color	<1.5	ASTM D1500
Viscosity@100°C cSt	11.2	ASTM D445
Viscosity@40°C cSt	79.99	ASTM D445

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information contained herein is subject to change without notice.

#### Health and Safety:

This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website. [www.royalmfg.com](http://www.royalmfg.com) or call (918)-584-2671.

#### Packaging Options:



55 Gal Drums



275/330 Gal Totes



Bulk

