

PRODUCT DATA SHEET

Hydraulic Jack Oil



PRODUCT DESCRIPTION:

Hydraulic Jack Oil is designed to lubricate the piston and seals of hydraulic jacks enabling them to perform in service without any leakage or loss of pressure.

KEY FEATURES:

- Piston and seal lubrication

CUSTOMER BENEFITS:

- Economic performance

APPLICATIONS:

Pistons and seals of hydraulic jacks

Typical Properties

Hydraulic Jack Oil		
Product Number	131	Test Method
API	24.41	
Specific Gravity	0.9076	ASTM 4052
Lbs/Gal	7.558	
Density	0.90709	
Flash Point °C	155	ASTM D92
Pour Point °C	-42	ASTM D97
Color	<2.5	ASTM D1500
Viscosity@100°C cSt	3.57	ASTM D445
Viscosity@40°C cSt	20.84	ASTM D445
Viscosity Index (VI)	0	ASTM D2270

Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Health and Safety:

When used for its intended application, this product is not expected to have any adverse health implications. For complete information on safe handling, as well as physical and chemical characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website, www.royalmfg.com, or call 918-584-2671. Do not use this product for purposes other than its intended use. Please be responsible to the environment when disposing of used product.