



Product Data Sheet



Royal Turbine Drip Oil

Turbine Drip Oil

PRODUCT DESCRIPTION:

Royal Turbine Drip Oil is a light bodied mineral oil for lubrication of vertical deep well pump bearings. It exhibits excellent low temperature fluidity, which assures adequate lubrication for the critical lower bearings even at low temperatures.

KEY FEATURES:

- Outstanding wear protection

CUSTOMER BENEFITS:

- Excellent low temperature fluidity

APPLICATIONS:

Well pump bearings

PACKAGING: Totes

and Drums



Product Data Sheet



Typical Properties

Royal Turbine Drip Oil		
Product Number	131	Test Method
API	23.4	
Viscosity@40°C cSt	18	ASTM D445
Viscosity@100°C cSt	3.4	ASTM D445
Viscosity@100°F SUS	97	
Viscosity@210°F SUS	38	
Viscosity Index (VI)	30	ASTM D2270
Pour Point °F	-45	ASTM D97
Lbs/Gal	13.8	
Flash Point °F	330	ASTM D92
Color	1.5	ASTM D1500

Typical Properties are typical of those obtained with normal production tolerance and do not constitute essentially a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice.

Health and Safety:

When used for its intended application, this product is not expected to have any adverse health implications. For complete information on safe handling, as well as physical and chemical characteristics please refer to the Material Safety Data Sheet (MSDS) found on our website, www.royalmfg.com, or call 918-584-2671. Do not use this product for purposes other than its intended use. Please be responsible to the environment when disposing of used product.

