



## X-140 Oil Improver

### *Gasoline Oil Conditioner*

**X-140 Oil Improver** is an oil soluble butadiene polymer type viscosity index improver for use as a supplement in lubricating oil. This oil improver will increase oil pressure without increasing carbon residue, reduce oil consumption, reduce engine wear, retard oil leakage and has good shear stability. **X-140 Oil Improver** may also be added to automatic transmissions, differentials and heavy duty gearboxes.

### Typical Properties

#### X-140 Oil Improver

Product Number	635	Test Method
Viscosity@40°C cSt	5860	ASTM D445
Viscosity@100°C cSt	550	ASTM 7042
Viscosity Index (VI)	250	ASTM D2270
API	28.0	-
Pour Point °C	20	ASTM D97
Flash Point °C	360	ASTM D92
Color	Amber	-

These properties are typical of the current production. Variations that do not affect product performance are to be expected depending on blending and manufacturing locations. The information above is subject to change without notice. **Packaging Options:**



Quarts



1 Gal. Jugs



5 Gal. Pails



55 Gal. Drums



275/330 Gal. Totes



>2,000 Gal. Bulk

#### Health and Safety:

This product is unlikely to have any adverse health implications or safety hazards when used for its intended application. Avoid contact with skin, use resistant gloves when handling used oil. If skin comes in contact wash immediately with soap and water. For complete information on safe handling and product characteristics please refer to the Safety Data Sheet (SDS) found on our website. [www.royalmfg.com](http://www.royalmfg.com) or call (918)-584-2671.